



Technical Bulletin

PHENOMENAL BRANDS, Phenoseal Products, A division of DAP Products Inc.
2400 Boston Street, Suite 200, Baltimore, Maryland 21224
Phone: 410-779-3265

Revised: 5/2/07

Phenoseal® Laminate Repair Filler

- Cured product is mold & mildew resistant
- Waterproof seal
- Easy water clean-up

Packaging: 1.7 fluid ounce (50 mL) squeeze tube
Colors: Light Almond, Dark Gray, Khaki
UPC Numbers: 0 51136 24124 9; 0 51136 24122 5; 0 51136 24120 1

Company Identification:

Manufacturer: PHENOMENAL BRANDS, Phenoseal Products, A division of DAP Products Inc.,
2400 Boston St., Baltimore, Maryland 21224

Usage Information: 410-779-3265 9:00 am to 7:00 pm EST.

Order Information: 410-779-3265

Also, visit the Phenoseal website at www.phenoseal.com

Product Description:

Phenoseal® Laminate Countertop Repair Filler is a premium acrylic-based product for filling chips, scratches, cuts, and seams in laminate kitchen countertops. It is a one-time use product designed to blend well with laminate countertop surfaces. It provides a durable waterproof seal and the cured product is mold and mildew resistant.

Suggested Uses:

Ideal for sealing laminate:

- Chips
- Scratches
- Cuts
- Seams

Adheres To:

- Laminate countertops
- Backsplashes

Performance Characteristics:

- Cured product is mold and mildew resistant.
- Tack free in 30 minutes.
- Easy water clean-up.

For Best Results:

Use in temperatures above 40°F.

Cold temperatures and high humidity will slow down cure time.

Store away from extreme heat or cold.

Surface Preparation & Application:

1. Surface must be clean and dry.
2. Cut nozzle at 45° angle to desired bead size.
3. Fill chip/scratch/seam w/ product.
4. For a neat finish, smooth the bead of caulk with a finishing tool.
5. Clean up excess w/ damp sponge before it skins over (15 minutes).
6. Allow caulk to dry for at least 12 hours, depending on temperature and humidity, before exposing to water or moisture.
7. Store away from extreme heat or cold.

Physical & Chemical Characteristics:

Vehicle:	Acrylic latex polymer
Filler:	Calcium Carbonate
Volatile:	Water
Solids:	81% ± 2%
Weight per Gallon:	13.8 ± .02 lbs./gal.
Service Temperature:	-20°F to 180°F
Temperature Application Range:	40°F to 100°F
Freeze Thaw Stability:	Passes 5 cycles
Flashpoint:	None
Shelf Life:	1 Year
Odor:	Very mild
Tooling Time:	10 minutes
Tack Free Time:	30 minutes
MSDS No:	00010061006

Clean Up:

Clean up excess uncured product with a damp sponge before it skins over (15 minutes). Wash hands with warm water and soap. Dried material must be cut or scraped away.

Safety:

See product label and Material Safety Data Sheet for safety information. You can request an MSDS by visiting our website at www.phenoseal.com or by calling 410-779-3265.

Satisfaction Guaranteed: If not satisfied with product's performance when used as directed, return used container and sales receipt to PHENOMENAL BRANDS, Technical Customer Service, 2400 Boston Street, Suite 200, Baltimore, MD 21224 for product replacement or sales price refund. PHENOMENAL BRANDS will not be liable for incidental or consequential damages.